

Safety Data Sheet ADHERGLASS



Safety Data Sheet dated 11/3/2024, Edition 2 - version 4
Regulation (EU) n. 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Identification of the mixture:

Trade name: ADHERGLASS

Trade code: 6624.372

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses:

Phenoxy primer.

User:

Consumer.

Professional.

Uses advised against:

All other uses.

1.3. Details of the supplier of the safety data sheet

Company:

BOERO BARTOLOMEO S.p.A. - Via Macaggi 19 - 16121 Genova - Tel. +39 010 55001 - Fax +39 010 5500305 - CF/P. IVA/REG. IMPRESE DI GENOVA 00267120103

Brand Veneziani TM used Under License of Colorificio Zetagi S.r.l.

Competent person responsible for the safety data sheet:

sicurezzaprodotti@boero.it

1.4. Emergency telephone number

Boero Bartolomeo S.p.A. - Tel.+39 010 55001

opening hours: Monday - Tuesday 9.00 am - 5.00 pm

UK: in an emergency the enquirer should call NHS 111/24/Direct (free-to-call medical helplines) or a doctor.

MALTA: tel. 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Flam. Liq. 2, H225 Highly flammable liquid and vapour.

Skin Irrit. 2, H315 Causes skin irritation.

Eye Dam. 1, H318 Causes serious eye damage.

Carc. 2, H351 Suspected of causing cancer.

STOT SE 3, H336 May cause drowsiness or dizziness.

STOT RE 2, H373 May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Hazard pictograms:



6624.372/4

Page n. 1 of 21

Safety Data Sheet

ADHERGLASS

Danger

Hazard statements:

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H351 Suspected of causing cancer.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/clothing, eye/face protection and hearing protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P370+P378 In case of fire use CO₂ or chemical powder. Never use water.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container according to local regulations.

Special Provisions:

- PACK2 The packing must have tactile indications of danger for blind people.

Contains

- butanone; ethyl methyl ketone
- 4-methylpentan-2-one; isobutyl methyl ketone
- 2-methoxy-1-methylethyl acetate
- 2-methylpropan-1-ol; iso-butanol

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

Adverse physicochemical, human health and environmental effects:

The main adverse physical-chemical effects for human health and the environment are listed in accordance with Sections 9 to 12 of the safety data sheet

No PBT, vPvB or endocrine disruptor substances present in concentration $\geq 0.1\%$

Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

6624.372/4

Page n. 2 of 21

Safety Data Sheet

ADHERGLASS

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

>= 20% - < 25% butanone; ethyl methyl ketone

REACH No.: 01-2119457290-43-XXXX, Index number: 606-002-00-3, CAS: 78-93-3, EC: 201-159-0

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

>= 15% - < 20% titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter <= 10 µm]

REACH No.: 01-2119489379-17-XXXX, CAS: 13463-67-7, EC: 236-675-5

Substance with a Union workplace exposure limit.

>= 10% - < 12.5% xylene [4]

REACH No.: 01-2119488216-32-XXXX, CAS: 1330-20-7, EC: 215-535-7

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

>= 7% - < 10% 4-methylpentan-2-one; isobutyl methyl ketone

REACH No.: 01-2119473980-30-XXXX, Index number: 606-004-00-4, CAS: 108-10-1, EC: 203-550-1

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Carc. 2 H351 Suspected of causing cancer.

Acute Tox. 4 H332 Harmful if inhaled.

STOT SE 3 H336 May cause drowsiness or dizziness.

Eye Irrit. 2 H319 Causes serious eye irritation.

EUH066 Repeated exposure may cause skin dryness or cracking.

Acute Toxicity Estimate:

ATE - Inhalation (Vapours) 11 mg/l

>= 5% - < 7% 2-methoxy-1-methylethyl acetate

REACH No.: 01-2119475791-29-XXXX, Index number: 607-195-00-7, CAS: 108-65-6, EC: 203-603-9

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

>= 3% - < 5% 2-methylpropan-1-ol; iso-butanol

REACH No.: 01-2119484609-23-XXXX, Index number: 603-108-00-1, CAS: 78-83-1, EC:

6624.372/4

Page n. 3 of 21

Safety Data Sheet ADHERGLASS

201-148-0

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H335 May cause respiratory irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

STOT SE 3 H336 May cause drowsiness or dizziness.

>= 2.5% - < 3% propan-2-ol; isopropyl alcohol; isopropanol

REACH No.: 01-2119457558-25-XXXX, Index number: 603-117-00-0, CAS: 67-63-0, EC: 200-661-7

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

>= 1% - < 2.5% crystalline silica

CAS: 14808-60-7, EC: 238-878-4

Substance with a Union workplace exposure limit.

>= 0.5% - < 1% free crystalline silica - respirable fraction

CAS: 14808-60-7, EC: 238-878-4

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

>= 0.05% - < 0.1% ethylbenzene

REACH No.: 01-2119489370-35-XXXX, Index number: 601-023-00-4, CAS: 100-41-4, EC: 202-849-4

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

STOT RE 2 H373 May cause damage to organs (auditive organs) through prolonged or repeated exposure.

Acute Tox. 4 H332 Harmful if inhaled.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

>= 0.0015% - < 0.01% methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate

REACH No.: 01-2119452498-28-xxxx, Index number: 607-035-00-6, CAS: 80-62-6, EC: 201-297-1

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

STOT SE 3 H335 May cause respiratory irritation.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

6624.372/4

Page n. 4 of 21

Safety Data Sheet

ADHERGLASS

In case of Ingestion:

Do NOT induce vomiting.

Give nothing to eat or drink.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

If breathing is irregular or stopped, administer artificial respiration.

Protective measures for first responders

Please refer to section 8.2 of this safety data sheet for the PPE required for first responder interventions.

4.2. Most important symptoms and effects, both acute and delayed

Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

In case of fire use CO₂ or chemical powder. Never use water.

Extinguishing media which must not be used for safety reasons:

Do not use water jets

None in particular.

5.2. Special hazards arising from the substance or mixture

Avoid inhaling the fumes.

5.3. Advice for firefighters

EQUIPMENT

Normal fire-fighting apparel, such as an open-circuit compressed air breathing apparatus (EN 137), flame-resistant coveralls (EN469), flame-resistant gloves (EN 659) and firefighter boots (HO A29 or A30).

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non emergency personnel:

Do not undertake any action that entails personal risk or without adequate training. Evacuate the surrounding areas. Do not touch or walk on spilled material. Wear suitable protective equipment (including the personal protective equipment under section 8.2 of this safety data sheet) to prevent contamination of skin, eyes and personal clothing. Wear a suitable breathing apparatus when ventilation is inadequate.

Do not inhale mist/vapours. Avoid dispersion of the product in the environment. Follow any relevant internal procedures for personnel not authorised to intervene directly in the case of accidental spillages.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

For emergency responders:

6624.372/4

Page n. 5 of 21

Safety Data Sheet ADHERGLASS

Block the leak if not hazardous. Evacuate unauthorised personnel. Wear suitable protective equipment (consult section 8.2 of this safety data sheet). Follow the relevant internal procedures for authorised personnel. Isolate the hazardous area and prevent entry. Ventilate closed spaces before entering.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

6.3. Methods and material for containment and cleaning up

Wash with plenty of water.

6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Adequately ventilated premises.

Advice on general occupational hygiene:

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Always keep the containers tightly closed.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Adequately ventilated premises.

7.3. Specific end use(s)

See section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butanone; ethyl methyl ketone - CAS: 78-93-3

EU - TWA(8h): 600 mg/m³, 200 ppm - STEL: 900 mg/m³, 300 ppm

ACGIH - TWA(8h): 200 ppm - STEL: 300 ppm - Notes: BEI - URT irr, CNS and PNS impair

VLE1 - TWA(8h): 600 mg/m³, 200 ppm

VLE - STEL: 900 mg/m³, 300 ppm

titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

EU - TWA(8h): 10 mg/m³

AGS - TWA(8h): 5 mg/m³

ACGIH - TWA(8h): 0.2 mg/m³ - Notes: Nanoscale particles; (R); A3 - LRT irr, pneumoconiosis

6624.372/4

Page n. 6 of 21

Safety Data Sheet ADHERGLASS

MAK - STEL: 3 mg/m³
ACGIH - TWA(8h): 2.5 mg/m³ - Notes: Finescale particles; (R); A3 - LRT irr, pneumoconiosis
HR - TWA(8h): 4 mg/m³ - Notes: (R respirabilna prašina)
HR - TWA(8h): 10 mg/m³ - Notes: (U ukupna prašina)
B TLV-TWA (8 hours) - TWA(8h): 10 mg/m³
DK TLV-TWA (8 hours) - TWA(8h): 6 mg/m³ - Notes: total dust
DK TLV-STEL (shterm) - STEL: 12 mg/m³ - Notes: total dust
FI TLV-TWA (8 hours) - TWA(8h): 11 mg/m³ - Notes: inhalable aerosol
DE TLV-TWA (8 hours) - TWA(8h): 0.3 mg/m³ - Notes: Respirable fraction, except ultrafine particles. Multiplied by the material density.
DE TLV-STEL - STEL: 2.4 mg/m³ - Notes: Respirable fraction, except ultrafine particles. Multiplied by the material density. 15 minutes average value.
IR TLV-TWA - TWA(8h): 10 mg/m³ - Notes: Inhalable fraction
LV TLV-TWA (8 hours) - TWA(8h): 10 mg/m³
NO TLV-TWA (8 hours) - TWA(8h): 5 mg/m³
PL TLV-TWA (8 hours) - TWA(8h): 10 mg/m³ - Notes: Inhalable fraction
RO TLV-TWA (8 hours) - TWA(8h): 10 mg/m³
RO TLV-STEL (shterm) - STEL: 15 mg/m³ - Notes: 15 minutes average value
ES TLV-TWA (8 hours) - TWA(8h): 10 mg/m³ - Notes: Inhalable fraction
MAK - TWA: 5 mg/m³ - Notes: inhalable aerosol
CH TLV-TWA (8 hours) - TWA(8h): 3 mg/m³ - Notes: respirable aerosol
GB TLV-TWA - TWA(8h): 10 mg/m³ - Notes: inhalable aerosol
GB TLV-TWA - TWA(8h): 4 mg/m³ - Notes: respirable aerosol
xylene [4] - CAS: 1330-20-7
EU - TWA(8h): 221 mg/m³, 50 ppm - STEL: 442 mg/m³, 100 ppm - Notes: skin
AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)
ACGIH - TWA(8h): 20 ppm - Notes: A4, BEI - URT and eye irr; hematologic eff; CNS impair
AGS - TWA(8h): 221 mg/m³ - STEL((15 min)): 442 mg/m³ - Notes: (Anm. H: Ämnet kan lätt upptas genom huden)
VLE1 - TWA(8h): 211 mg/m³, 50 ppm
VLE - STEL: 442 mg/m³, 100 ppm - Notes: Skin
4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
EU - TWA(8h): 83 mg/m³, 20 ppm - STEL: 208 mg/m³, 50 ppm
ACGIH - TWA(8h): 20 ppm - STEL: 75 ppm - Notes: A3, BEI - URT irr, dizziness, headache
VLE1 - TWA(8h): 83 mg/m³, 20 ppm
VLE - STEL: 208 mg/m³, 50 ppm
2-methoxy-1-methylethyl acetate - CAS: 108-65-6
EU - TWA(8h): 275 mg/m³, 50 ppm - STEL: 550 mg/m³, 100 ppm - Notes: Skin
HR - TWA(8h): 275 mg/m³, 50 ppm
HRKGV1 - STEL: 550 mg/m³, 100 ppm
2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
ACGIH - TWA(8h): 50 ppm - Notes: Skin and eye irr
VLE1 - TWA: 154 mg/m³, 50 ppm
VLE - STEL: 231 mg/m³, 75 ppm
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

6624.372/4

Page n. 7 of 21

Safety Data Sheet ADHERGLASS

ACGIH - TWA(8h): 200 ppm - STEL: 400 ppm - Notes: A4, BEI - Eye and URT irr, CNS impair

VLE1 - TWA: 999 mg/m³, 400 ppm

VLE - STEL: 1250 mg/m³, 500 ppm

crystalline silica - CAS: 14808-60-7

EU - TWA(8h): 0.1 mg/m³

ACGIH - TWA(8h): 0.025 mg/m³ - Notes: (R), A2 - Pulm fibrosis, lung cancer

AGS - TWA(8h): 0.2 mg/m³ - Notes: mg fiber/cm³ (Anm. C: Ämnet är cancerframkallande, M: Medicinsk kontroll kan krävas för hantering av ämnet.)

MAK - STEL: 0.15 mg/m³

HR - TWA(8h): 0.1 mg/m³

AT TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: MAK value. Respirable fraction.

B TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable dust.

DK TLV-TWA (8 hours) - TWA(8h): 0.3 mg/m³ - Notes: Inhalable aerosol

DK TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable aerosol

DK TLV-STEL (shterm) - STEL: 0.6 mg/m³ - Notes: Inhalable aerosol

DK TLV-STEL (shterm) - STEL: 0.3 mg/m³ - Notes: Respirable aerosol

FI TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction.

FR TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

DE TLV-TWA(8hAGS) - TWA(8h): 0.05 mg/m³ - Notes: Assessment standard, see Technical Rules for Hazardous Substances (TRGS) 559 "Dust containing quartz". Respirable fraction.

DE TLV-STEL(stAGS) - STEL: 0.4 mg/m³ - Notes: Assessment standard, see Technical Rules for Hazardous Substances (TRGS) 559 "Dust containing quartz". Respirable fraction. 15 minutes average value.

HU TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

IR TLV-TWA - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

NO TLV-TWA (8 hours) - TWA(8h): 0.3 mg/m³ - Notes: Inhalable fraction

NO TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction

PL TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

ES TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction.

MAK - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

CH TLV-TWA (8 hours) - TWA(8h): 0.15 mg/m³ - Notes: respirable aerosol

NL TLV-TWA (8 hours) - TWA(8h): 0.075 mg/m³ - Notes: Respirable fraction.

free crystalline silica - respirable fraction - CAS: 14808-60-7

EU - TWA(8h): 0.1 mg/m³

ACGIH - TWA(8h): 0.025 mg/m³ - Notes: (R), A2 - Pulm fibrosis, lung cancer

AGS - TWA(8h): 0.2 mg/m³ - Notes: mg fiber/cm³ (Anm. C: Ämnet är cancerframkallande, M: Medicinsk kontroll kan krävas för hantering av ämnet.)

MAK - STEL: 0.15 mg/m³

HR - TWA(8h): 0.1 mg/m³

AT TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: MAK value. Respirable fraction.

B TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable dust.

DK TLV-TWA (8 hours) - TWA(8h): 0.3 mg/m³ - Notes: Inhalable aerosol

DK TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable aerosol

DK TLV-STEL (shterm) - STEL: 0.6 mg/m³ - Notes: Inhalable aerosol

DK TLV-STEL (shterm) - STEL: 0.3 mg/m³ - Notes: Respirable aerosol

FI TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction.

FR TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

Safety Data Sheet ADHERGLASS

DE TLV-TWA(8hAGS) - TWA(8h): 0.05 mg/m³ - Notes: Assessment standard, see Technical Rules for Hazardous Substances (TRGS) 559 "Dust containing quartz". Respirable fraction.

DE TLV-STEL(stAGS) - STEL: 0.4 mg/m³ - Notes: Assessment standard, see Technical Rules for Hazardous Substances (TRGS) 559 "Dust containing quartz". Respirable fraction. 15 minutes average value.

HU TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

IR TLV-TWA - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

NO TLV-TWA (8 hours) - TWA(8h): 0.3 mg/m³ - Notes: Inhalable fraction

NO TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction

PL TLV-TWA (8 hours) - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

ES TLV-TWA (8 hours) - TWA(8h): 0.05 mg/m³ - Notes: Respirable fraction.

MAK - TWA(8h): 0.1 mg/m³ - Notes: Respirable fraction.

CH TLV-TWA (8 hours) - TWA(8h): 0.15 mg/m³ - Notes: respirable aerosol

NL TLV-TWA (8 hours) - TWA(8h): 0.075 mg/m³ - Notes: Respirable fraction.

ethylbenzene - CAS: 100-41-4

EU - TWA(8h): 442 mg/m³, 100 ppm - STEL: 884 mg/m³, 200 ppm - Notes: Skin

AGS - TWA(8h): 200 mg/m³ - STEL((15 min)): 450 mg/m³

ACGIH - TWA(8h): 20 ppm - Notes: OTO; A3, BEI - URT & eye irr; ototoxicity; kidney eff; CNS impair

VLE1 - TWA(8h): 442 mg/m³, 100 ppm

VLE - STEL: 884 mg/m³, 200 ppm

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6

EU - TWA(8h): 50 ppm - STEL: 100 ppm

ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: DSEN, A4 - URT and eye irr, body weight eff, pulm edema.

AT TLV-TWA (8 hours) - TWA(8h): 210 mg/m³, 50 ppm

AT TLV-STEL (shterm) - STEL: 420 mg/m³, 100 ppm

B TLV-TWA (8 hours) - TWA(8h): 208 mg/m³, 50 ppm

B TLV-STEL (sh term) - STEL: 416 mg/m³, 100 ppm - Notes: 15 minutes average value.

DK TLV-TWA (8 hours) - TWA(8h): 102 mg/m³, 25 ppm - Notes: Skin.

DK TLV-STEL (shterm) - STEL: 204 mg/m³, 50 ppm - Notes: Skin. 15 minutes average value.

FI TLV-TWA (8 hours) - TWA(8h): 42 mg/m³, 10 ppm

FI TLV-STEL (shterm) - STEL: 410 mg/m³, 100 ppm - Notes: 15 minutes average value.

FR TLV-TWA (8 hours) - TWA(8h): 205 mg/m³, 50 ppm

FR TLV-STEL (shterm) - STEL: 410 mg/m³, 100 ppm - Notes: Restrictive statutory limit values Skin. 15 minutes average value.

DE TLV-TWA(8hAGS) - TWA(8h): 210 mg/m³, 50 ppm

DE TLV-STEL(stAGS) - STEL: 420 mg/m³, 100 ppm - Notes: 15 minutes average value.

DE TLV-TWA (8 hours) - TWA(8h): 210 mg/m³, 50 ppm

DE TLV-STEL(stAGS) - STEL: 420 mg/m³, 100 ppm - Notes: 15 minutes average value.

HU TLV-TWA (8 hours) - TWA(8h): 208 mg/m³ - Notes: Skin.

HU TLV-STEL (shterm) - STEL: 415 mg/m³ - Notes: Skin. 15 minutes average value.

IR TLV-TWA - TWA(8h): 50 mg/m³

IR TLV-STEL - STEL: 100 mg/m³ - Notes: 15 minutes reference period.

VLE1 - TWA(8h): 50 mg/m³

VLE - STEL: 100 mg/m³ - Notes: 15 minutes average value.

LV TLV-TWA (8 hours) - TWA(8h): 10 mg/m³

Safety Data Sheet ADHERGLASS

NO TLV-TWA (8 hours) - TWA(8h): 100 mg/m³, 25 ppm
NO TLV-STE (shterm) - STEL: 400 mg/m³, 100 ppm - Notes: 15 minutes average value.
PL TLV-TWA (8 hours) - TWA(8h): 100 mg/m³
PL TLV-STE (shterm) - STEL: 300 mg/m³ - Notes: 15 minutes average value.
RO TLV-TWA (8 hours) - TWA(8h): 205 mg/m³, 50 ppm
RO TLV-STE (shterm) - STEL: 410 mg/m³, 100 ppm - Notes: 15 minutes average value.
ES TLV-TWA (8 hours) - TWA(8h): 100 mg/m³, 50 ppm
ES TLV-STE (shterm) - STEL: 416 mg/m³, 100 ppm - Notes: 15 minutes average value.
MAK - TWA(8h): 200 mg/m³, 50 ppm - STEL: 400 mg/m³, 100 ppm - Notes: 15 minutes average value.
CH TLV-TWA (8 hours) - TWA(8h): 210 mg/m³, 50 ppm
CH TLV-STE (shterm) - STEL: 420 mg/m³, 100 ppm
NL TLV-TWA (8 hours) - TWA(8h): 205 mg/m³, 50 ppm
NL TLV-STE (shterm) - STEL: 410 mg/m³, 100 ppm - Notes: 15 minutes average value.
GB TLV-TWA - TWA(8h): 208 mg/m³, 50 ppm - Notes: 1
GB TLV-STE - STEL: 416 mg/m³, 100 ppm - Notes: 15 minutes average value.
HR - TWA(8h): 50 mg/m³
HRKGV I - STEL: 100 mg/m³

DNEL Exposure Limit Values

titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

Worker Industry: 10 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, local effects

Consumer: 700 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

xylene [4] - CAS: 1330-20-7

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, systemic effects

Worker Industry: 289 mg/m³ - Consumer: 174 mg/m³ - Exposure: Human Inhalation - Frequency: Short Term, local effects

Worker Industry: 180 mg/kg - Consumer: 108 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 77 mg/m³ - Consumer: 14.8 mg/m³ - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.6 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Worker Industry: 153.5 mg/kg - Worker Professional: 153.5 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Worker Industry: 275 mg/kg - Worker Professional: 275 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 54.8 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects

Consumer: 33 mg/kg - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Consumer: 1.67 mg/kg - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter <= 10 µm] - CAS: 13463-67-7

Target: Marine water - Value: 1 mg/L

Target: Fresh Water - Value: 0.127 mg/L

Target: Microorganisms in sewage treatments - Value: 100 mg/L

6624.372/4

Page n. 10 of 21

Safety Data Sheet ADHERGLASS

Target: Marine water sediments - Value: 100 mg/kg

Target: Freshwater sediments - Value: 1000 mg/kg

xylene [4] - CAS: 1330-20-7

Target: Fresh Water - Value: 0.327 mg/L

Target: Marine water - Value: 0.327 mg/L

Target: Freshwater sediments - Value: 12.46 mg/kg

Target: Marine water sediments - Value: 12.46 mg/kg

Target: Microorganisms in sewage treatments - Value: 6.58 mg/L

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

Target: Fresh Water - Value: 0.635 mg/L

Target: Marine water - Value: 0.0635 mg/L

Target: Microorganisms in sewage treatments - Value: 100 mg/L

Target: Freshwater sediments - Value: 3.29 mg/kg

Target: Marine water sediments - Value: 0.329 mg/kg

Biological Exposure Index

butanone; ethyl methyl ketone - CAS: 78-93-3

Value: 2.6 mgg creatinina - medium: Urine - Biological Indicator: MEK in urine - Sampling Period: End of turn

xylene [4] - CAS: 1330-20-7

Value: 1.50 mg/L - medium: Blood - Sampling Period: End of turn

Value: 1.50 gg creatinina - medium: Blood - Sampling Period: End of turn

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

Value: 3.5 mg/L - medium: Urine - Sampling Period: Not critical

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

Value: 50 mg/L - medium: Blood - Biological Indicator: Acetone in blood - Sampling Period: End of turn

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate - CAS: 80-62-6

Value: 120 mg/g - medium: Urine - Biological Indicator: 76 - Sampling Period: End of turn

8.2. Exposure controls

Appropriate engineering controls:

Given that the use of appropriate technical measures should always take priority over personal protective equipment, ensure good ventilation in the workplace through effective on-site extraction ventilation.

Personal protective equipment must bear CE marking certifying conformity with the standards in force.

Provide an emergency shower with an eyewash station.

Exposure levels should be kept as low as possible to avoid significant accumulation in the body.

Manage personal protective equipment in order to ensure maximum protection (e.g. reducing replacement times).

Eye protection:

Use goggles/facemask certified UNI EN 166.

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Suitable protective clothing is required for complete skin protection: for example coveralls with long sleeves and trousers, rubber boots and apron, etc., according to UNI EN 14325.

Protection for hands:

Use protective gloves: waterproof rubber gloves certified UNI EN 374. Nitrile gloves provide good protection. Use care in selecting a penetration time of the gloves longer than the foreseen usage time.

Respiratory protection:

6624.372/4

Safety Data Sheet

ADHERGLASS

Use adequate protective respiratory equipment: a carbon filter mask with filters certified UNI EN 149 or dust masks certified UNI EN 140. Filters of types A and P types may be considered.

Thermal Hazards:

None

Environmental exposure controls:

See sections 6 and 13

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Physical state:	Liquid	--	--
Colour:	pink	--	--
Odour:	solvent-like	--	--
Melting point/freezing point:	N.A.	--	--
Boiling point or initial boiling point and boiling range:	N.A.	--	--
Flammability:	Flam. Liq. 2, H225	--	--
Lower and upper explosion limit:	N.A.	--	--
Flash point:	6 °C	--	--
Auto-ignition temperature:	6 °C	--	--
Decomposition temperature:	N.A.	--	--
pH:	N.A.	--	--
Kinematic viscosity:	> 20,5 mm ² /sec (40 °C)	--	--
Viscosity (23°C±0.5°C)	min 14- max 16	SPECIFIC WEIGHT BY MEANS OF PICNOMETER (gr / cm ³).	--
Spindle:	0	--	--
Speed (rpm):	0	--	--
Solubility in water:	insoluble	--	--

6624.372/4

Page n. 12 of 21

Safety Data Sheet

ADHERGLASS

Partition coefficient n-octanol/water (log value):	N.A.	--	--
Vapour pressure:	N.A.	--	--
Density and/or relative density:	1.2090	--	--
Relative vapour density:	N.A.	--	--
Particle characteristics:			
Particle size:	N.A.	--	--

9.2. Other information

No other relevant information

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction to report under normal conditions of use and storage (refer to section 7.2)

10.2. Chemical stability

The product is stable under normal conditions of use and storage (refer to section 7.2).

10.3. Possibility of hazardous reactions

None under normal conditions of use and storage (refer to section 7.2). Always keep containers tightly sealed.

10.4. Conditions to avoid

Keep away from naked flames, sparks and heat sources. Avoid exposure to direct sunlight.

10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

10.6. Hazardous decomposition products

Gases and vapours potentially harmful to health may be released through thermal decomposition or in the event of fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Toxicological information of the product:

ADHERGLASS

a) acute toxicity

Not classified

Based on available data, the classification criteria are not met

b) skin corrosion/irritation

The product is classified: Skin Irrit. 2 H315

c) serious eye damage/irritation

The product is classified: Eye Dam. 1 H318

d) respiratory or skin sensitisation

Not classified

Based on available data, the classification criteria are not met

6624.372/4

Page n. 13 of 21

Safety Data Sheet ADHERGLASS

- e) germ cell mutagenicity
Not classified
Based on available data, the classification criteria are not met
- f) carcinogenicity
The product is classified: Carc. 2 H351
- g) reproductive toxicity
Not classified
Based on available data, the classification criteria are not met
- h) STOT-single exposure
The product is classified: STOT SE 3 H336
- i) STOT-repeated exposure
The product is classified: STOT RE 2 H373
- j) aspiration hazard
Not classified
Based on available data, the classification criteria are not met

Toxicological information of the main substances found in the product:

butanone; ethyl methyl ketone - CAS: 78-93-3

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 2054 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 10 ml/kg

c) serious eye damage/irritation:

Test: Eye Irritant - Species: rabbit

titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - CAS: 13463-67-7

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 10.000 mg/kg

xylene [4] - CAS: 1330-20-7

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 3523 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 2000 mg/kg

Test: LC50 - Route: inhalation - Species: rat > 27.571 mg/l - Duration: 4h

b) skin corrosion/irritation:

Test: Skin Irritant Positive

c) serious eye damage/irritation:

Test: Eye Irritant Positive

4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1

a) acute toxicity

ATE - Inhalation (Vapours) 11 mg/l

Test: LD50 - Route: oral - Species: rat = 2080 mg/kg

Test: LD50 - Route: dermal - Species: rabbit > 20 ml/kg

Test: LC50 - Route: inhalation - Species: rat = 2000-4000 Ppm - Duration: 4h

d) respiratory or skin sensitisation:

Test: Respiratory Tract Irritant

2-methoxy-1-methylethyl acetate - CAS: 108-65-6

a) acute toxicity:

Test: LD50 - Route: oral - Species: rat > 5000 mg/kg

Test: LC50 - Route: inhalation - Species: rat > 10.6 mg/kg

Safety Data Sheet ADHERGLASS

- Test: LD50 - Route: dermal - Species: rat > 2000 mg/kg
- b) skin corrosion/irritation:
Test: Skin Corrosive - Species: rabbit Negative
2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
- a) acute toxicity:
Test: LD50 - Route: oral - Species: rat > 2830 mg/kg
Test: LD50 - Route: dermal - Species: rabbit > 2000 mg/kg
Test: LC50 - Route: inhalation - Species: rat = 24.6 mg/l - Duration: 4h
- b) skin corrosion/irritation:
Test: Skin Irritant - Species: rabbit
- c) serious eye damage/irritation:
Test: Eye Corrosive - Species: rabbit
propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- a) acute toxicity:
Test: LD50 - Route: oral - Species: rat = 5840 mg/kg
Test: LC50 - Route: inhalation - Species: rat > 10000 Ppm - Duration: 18207.6h
Test: LD50 - Route: dermal - Species: rabbit = 16.4 ml/kg
- b) skin corrosion/irritation:
Test: Skin Corrosive - Route: dermal - Species: rabbit Negative - Notes: OECD 404
- c) serious eye damage/irritation:
Test: Eye Corrosive - Species: rabbit Positive - Notes: OECD 405
ethylbenzene - CAS: 100-41-4
- a) acute toxicity:
Test: LC50 - Route: inhalation - Species: rat = 17.2 mg/l - Duration: 4h

11.2. Information on other hazards

Endocrine disrupting properties:

No endocrine disruptor substances present in concentration $\geq 0.1\%$

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ADHERGLASS

Not classified for environmental hazards

Based on available data, the classification criteria are not met

butanone; ethyl methyl ketone - CAS: 78-93-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2993 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 308 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae = 2029 mg/l - Duration h: 96

titanium dioxide; [in powder form containing less than 1 % of particles with aerodynamic diameter $\leq 10 \mu\text{m}$] - CAS: 13463-67-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: OECD 203

Endpoint: LC50 - Species: Daphnia > 100 mg/l - Duration h: 48 - Notes: OECD 202

xylene [4] - CAS: 1330-20-7

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 2.6 ml/l - Duration h: 96

6624.372/4

Page n. 15 of 21

Safety Data Sheet ADHERGLASS

- Endpoint: EC50 - Species: Algae = 2.2 mg/l - Duration h: 72
- b) Aquatic chronic toxicity:
- Endpoint: NOEC - Species: Fish > 1.3 mg/l - Notes: 56 d
- Endpoint: NOEC - Species: Daphnia = 0.74 mg/l - Notes: 7 d
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish > 179 mg/l - Duration h: 96
- Endpoint: EC50 - Species: Daphnia > 200 mg/l - Duration h: 48
- Endpoint: NOEC - Species: Algae > 146 mg/l - Notes: 7 d
- 2-methoxy-1-methylethyl acetate - CAS: 108-65-6
- a) Aquatic acute toxicity:
- Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72
- Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96
- Endpoint: EC50 - Species: Daphnia > 400 mg/l - Duration h: 48
- 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish = 1430 mg/l - Duration h: 96
- Endpoint: EC50 - Species: Daphnia = 1100 mg/l - Duration h: 48
- Endpoint: EC50 - Species: Algae = 1799 mg/l - Duration h: 72
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- a) Aquatic acute toxicity:
- Endpoint: LC50 - Species: Fish = 9640 mg/l - Duration h: 96
- Endpoint: EC50 - Species: Daphnia > 10000 mg/l - Duration h: 24
- Endpoint: EC50 - Species: Algae = 1800 mg/l - Duration h: 168
- 12.2. Persistence and degradability
- There is no data available on the preparation itself.
- butanone; ethyl methyl ketone - CAS: 78-93-3
- Biodegradability: Readily biodegradable - Test: CO2 production - %: 98 - Notes: 28 d
- xylene [4] - CAS: 1330-20-7
- Biodegradability: Readily biodegradable - Notes: solubilita' in acqua=146 mg/l
- 4-methylpentan-2-one; isobutyl methyl ketone - CAS: 108-10-1
- Biodegradability: Readily biodegradable
- 2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1
- Biodegradability: Readily biodegradable - %: 90 - Notes: 14 d
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- Biodegradability: Readily biodegradable - %: 70 - Notes: 10 d
- 12.3. Bioaccumulative potential
- There is no data available on the preparation itself.
- xylene [4] - CAS: 1330-20-7
- Test: Kow - Partition coefficient 3.2 - Notes: mg/l
- Test: BCF - Bioconcentration factor 25.9 - Notes: mg/l
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
- Test: Kow - Partition coefficient 0.05 - Notes: mg/l
- ethylbenzene - CAS: 100-41-4
- Test: Kow - Partition coefficient 3.6
- 12.4. Mobility in soil
- There is no data available on the preparation itself.
- xylene [4] - CAS: 1330-20-7
- Test: Koc 2.73 - Notes: mg/l

6624.372/4

Safety Data Sheet

ADHERGLASS

- 12.5. Results of PBT and vPvB assessment
vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties
No endocrine disruptor substances present in concentration $\geq 0.1\%$
- 12.7. Other adverse effects
None

SECTION 13: Disposal considerations

- 13.1. Waste treatment methods
Recover if possible. In so doing, comply with the local and national regulations currently in force.
Directives 91/156/CEE, 91/689/CEE, 94/62/CE.
EWC CODE 080111
Do not empty into drains, ground or waterways. Dispose of product residues and related containers at a collection point for hazardous or special waste or, where appropriate, through an authorized waste disposal company.

SECTION 14: Transport information



- 14.1. UN number or ID number
- | | |
|-----------------|------|
| ADR-UN Number: | 1263 |
| IATA-UN Number: | 1263 |
| IMDG-UN Number: | 1263 |
- 14.2. UN proper shipping name
- | | |
|---------------------|-------|
| ADR-Shipping Name: | PAINT |
| IATA-Shipping Name: | PAINT |
| IMDG-Shipping Name: | PAINT |
- 14.3. Transport hazard class(es)
- | | |
|-------------------------------------|---------|
| ADR-Class: | 3 |
| UN no.: | UN 1263 |
| ADR - Hazard identification number: | 33 |
| IATA-Class: | 3 |
| IATA-Label: | 3 |
| IMDG-Class: | 3 |
| Erg-code: | 3L |
- 14.4. Packing group
- | | |
|---------------------|----|
| ADR-Packing Group: | II |
| IATA-Packing group: | II |
| IMDG-Packing group: | II |

6624.372/4

Page n. 17 of 21

Safety Data Sheet ADHERGLASS

14.5. Environmental hazards

ADR-Environmental Pollutant: No
IMDG-Marine pollutant: No
IMDG-EmS: F-E,
S-E

14.6. Special precautions for user

ADR-Subsidiary hazards: -
ADR-S.P.: 163 367 640C 650
ADR-Transport category (Tunnel restriction code): 2 (D/E)
ADR-Limited Quantities: 5 L
ADR-Excepted Quantities: E2
IATA-Passenger Aircraft: 353
IATA-Subsidiary hazards: -
IATA-Cargo Aircraft: 364
IATA-S.P.: A3 A72 A192
IATA-ERG: 3L
IMDG-Subsidiary hazards: -
IMDG-Stowage and handling: Category B
IMDG-Segregation: -

14.7. Maritime transport in bulk according to IMO instruments

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EU) n. 2020/878

Dir. 89/391/CEE and subsequent amendments (Risks related to chemical agents at work and Occupational exposure limit values). Directive 1999/13/EC and subsequent amendments (limitation of emissions of volatile organic compounds due to the use of organic solvents in certain activities and installations). Regulation (CE) n. 1907/2006 , Regulation (CE) 830/2015 and subsequent amendments (concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals - REACH). Regulation (CE) n.1272/2008 and subsequent amendments (on classification, labeling and packaging of substances and mixtures - CLP).

International Maritime Dangerous Goods Code, IATA Dangerous Goods Regulation, International Carriage of Dangerous Goods by Road (ADR).

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 3

Restriction 40

Restrictions related to the substances contained:

Restriction 30

Restriction 75

Restriction 3 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Restriction 40 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

Restriction 75 is not applicable because the mixture does not fall within the restrictions mentioned in Annex XVII of EC Regulation No. 1907/2006.

6624.372/4

Page n. 18 of 21

Safety Data Sheet

ADHERGLASS

Where applicable, refer to the following regulatory provisions :

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products. Regulation UE No 649/2012 concerning the export and import of dangerous chemicals. Regulation UE n. 528/2012 concerning the making available on the market and use of biocidal products.

Directive 2012/18/EU (Seveso III)

Regulation (EC) No. 648/2004 (detergents).

Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products.

Regulation (EC) No 689/2006 concerning the export and import of dangerous chemicals.

Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

Seveso III category according to Annex 1, part 1

Product belongs to category: P5c

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Hazard class and hazard category	Code	Description
Flam. Liq. 2	2.6/2	Flammable liquid, Category 2
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 4	3.1/4/Dermal	Acute toxicity (dermal), Category 4
Acute Tox. 4	3.1/4/Inhal	Acute toxicity (inhalation), Category 4
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Irrit. 2	3.2/2	Skin irritation, Category 2
Eye Dam. 1	3.3/1	Serious eye damage, Category 1
Eye Irrit. 2	3.3/2	Eye irritation, Category 2
Skin Sens. 1	3.4.2/1	Skin Sensitisation, Category 1
Carc. 2	3.6/2	Carcinogenicity, Category 2
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure, Category 3
STOT RE 1	3.9/1	Specific target organ toxicity - repeated exposure, Category 1
STOT RE 2	3.9/2	Specific target organ toxicity - repeated

6624.372/4

Page n. 19 of 21

Safety Data Sheet

ADHERGLASS

		exposure, Category 2
Aquatic Chronic 3	4.1/C3	Chronic (long term) aquatic hazard, category 3

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Flam. Liq. 2, H225	On basis of test data
Skin Irrit. 2, H315	Calculation method
Eye Dam. 1, H318	Calculation method
Carc. 2, H351	Calculation method
STOT SE 3, H336	Calculation method
STOT RE 2, H373	Calculation method

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,
Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE: Acute Toxicity Estimate
ATEmix: Acute toxicity Estimate (Mixtures)
CAS: Chemical Abstracts Service (division of the American Chemical Society).
CLP: Classification, Labeling, Packaging.
DNEL: Derived No Effect Level.
EINECS: European Inventory of Existing Commercial Chemical Substances.
GefStoffVO: Ordinance on Hazardous Substances, Germany.
GHS: Globally Harmonized System of Classification and Labeling of Chemicals.
IATA: International Air Transport Association.
IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

6624.372/4

Page n. 20 of 21

Safety Data Sheet ADHERGLASS

	Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.